



OVERALL WIDTH: 5.594"  
1/2 OF FACE: 1.875"  
L MEASUREMENT: 2.375"  
WEB-TO-HUB EXTENSION R: 2.054"  
FACE-TO-HUB EXTENSION L: 1.094"  
FACE-TO-HUB EXTENSION R: 1.844"  
APPROXIMATE WEIGHT (LBS.): 21  
SMALL BORE DIAMETER: 2.406"

TOLERANCES:  
WHEEL DIAMETER: +0.005"/-0.000"  
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B	B	S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
10.000"	3.750"	3.719"	4.500"	2.875"	1.250"	0.500"	0.250"
<p>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</p> <p>DIMENSIONS: <math>\pm 0.010</math>"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p><b>BRAKE PRODUCTS, INC.</b> 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: <a href="http://www.brakeproducts.com">www.brakeproducts.com</a> Email: <a href="mailto:sales@brakeproducts.com">sales@brakeproducts.com</a> Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Saturday, Oct 28 2017</p>				<p>506, 508, 608 MOTOR 38 LBS</p>		<p><b>PART #</b> BE101006</p>	
<p><b>DESCRIPTION:</b> 10 INCH BORED &amp; KEYED BRAKE WHEEL</p>				<p><b>MATERIAL SPECIFICATION:</b> DUCTILE IRON ASTM A536-84 80-55-06</p>		<p><b>SERIAL #</b> 334</p>	