



OVERALL WIDTH: 6.125"
1/2 OF FACE: 1.875"
L MEASUREMENT: 2.000"
WEB-TO-HUB EXTENSION R: 1.333"
FACE-TO-HUB EXTENSION L: 2.875"
FACE-TO-HUB EXTENSION R: 2.375"
APPROXIMATE WEIGHT (LBS.): 31
SMALL BORE DIAMETER: 1.537"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B	BORE TAPER IN/FT	S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER		KEYWAY WIDTH	KEYWAY DEPTH
10.000"	3.750"	4.250"	3.250"	1.875"	1.250"	0.500"	0.250"
<p>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</p> <p>DIMENSIONS: $\pm 0.010"$</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p>BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p> <p>326TX CR22 129B5631P12 ALLI C7500-1T IP20172 BRIDGE</p>		<p>Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
DATE: Saturday, Oct 28 2017				PART # BE101013		MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06	
DESCRIPTION: 10 INCH BORED & KEYED BRAKE WHEEL						SERIAL # 0	