


OVERALL WIDTH: 8.250"
1/2 OF FACE: 2.875"
L MEASUREMENT: 3.500"
WEB-TO-HUB EXTENSION R: 2.585"
FACE-TO-HUB EXTENSION L: 3.250"
FACE-TO-HUB EXTENSION R: 2.500"
APPROXIMATE WEIGHT (LBS.): 55
SMALL BORE DIAMETER: 3.104"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
13.000"	5.750"	5.375"	5.000"	3.625"	1.250"	0.750"	0.250"

UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES

DIMENSIONS: ± 0.010 "
FINISH: 250  EXCEPT FOR BORE AND OUTER

FACE WHICH SHOULD BE 63 

BRAKE PRODUCTS, INC.
16751 HILLTOP PARK PLACE
CHAGRIN FALLS, OH 44023
UNITED STATES OF AMERICA

Web: www.brakeproducts.com
Email: sales@brakeproducts.com
Phone: (440) 543-7962
Fax: (440) 543-7963

HUB LENGTH BORE & KEYWAY FOR 412, 612, 812, AC25, AC30, MCS12, MD412AE, MD412AE2
SW50 AISE STANDARD OFFSET OF 5.375
171B3452P20 GH505LXC05 E013520 364388

DATE: Sunday, Nov 19 2017	PART # BE131006	MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06
DESCRIPTION: 13 INCH BORED & KEYED BRAKE WHEEL		SERIAL # 0