



OVERALL WIDTH: 17.375"
1/2 OF FACE: 7.125"
L MEASUREMENT: 6.750"
WEB-TO-HUB EXTENSION R: 2.947"
FACE-TO-HUB EXTENSION L: 10.625"
FACE-TO-HUB EXTENSION R: 3.125"
APPROXIMATE WEIGHT (LBS.): 665
SMALL BORE DIAMETER: 5.172"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B	B	S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
30.000"	14.250"	10.250"	6.750"	5.875"	1.250"	1.500"	0.750"
<p>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</p> <p>DIMENSIONS: ± 0.010"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p>BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Thursday, Oct 26 2017</p>				<p>PART # BE301004</p>		<p>MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06</p>	
<p>DESCRIPTION: 30 INCH BORED & KEYED BRAKE WHEEL</p>						<p>SERIAL # 0</p>	

HUB LENGTH BORE & KEYWAY FOR A 620 MILL MOTOR
AISE STANDARD OFFSET OF 10.25 INCHES
1258529 GH505-RX-G03 139B8184P1 291-AS-70-8841-7D