



OVERALL WIDTH: 5.625"  
1/2 OF FACE: 1.625"  
L MEASUREMENT: 1.500"  
WEB-TO-HUB EXTENSION R: 2.356"  
FACE-TO-HUB EXTENSION L: 1.625"  
FACE-TO-HUB EXTENSION R: 2.375"  
APPROXIMATE WEIGHT (LBS.): 7  
SMALL BORE DIAMETER: 2.083"

TOLERANCES:  
WHEEL DIAMETER: +0.005"/-0.000"  
BORE TAPER: +0.000"/-0.003"

**APPROVED BY:** \_\_\_\_\_ **SIGNATURE:** \_\_\_\_\_ **DATE:** \_\_\_\_\_

D	F	O	H	B	B	S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
8.000"	3.250"	4.000"	4.000"	2.500"	1.250"	0.500"	0.250"

UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES

DIMENSIONS:  $\pm 0.010"$   
FINISH: 250  EXCEPT FOR BORE AND OUTER  
FACE WHICH SHOULD BE 63 

**BRAKE PRODUCTS, INC.**  
16751 HILLTOP PARK PLACE  
CHAGRIN FALLS, OH 44023  
UNITED STATES OF AMERICA

Web: [www.brakeproducts.com](http://www.brakeproducts.com)  
Email: [sales@brakeproducts.com](mailto:sales@brakeproducts.com)  
Phone: (440) 543-7962  
Fax: (440) 543-7963

Motor Frame: 606, AC8

**DATE:** Monday, May 23 2016 **PART #** BE081016 **MATERIAL SPECIFICATION:** DUCTILE IRON ASTM A536-84 80-55-06

**DESCRIPTION:** 8 INCH BRAKE WHEEL **SERIAL #** 0